

ACUTE-08/AMP

100+50W bi-amplified active speakers

A very compact speaker. 100W amplifier + 50 W HF amplifier

ref 8738

ACUTE-10/AMP

200+50W active speaker

A 250W LF amplifier + a 50W HF amplifier for a great rendering in a compact size speaker

ref 9703

ACUTE-12/AMP

300 W + 250 W active speaker

12" active speaker bi- amplified - 300W boomer + 50 W HF driver

ref 8673

ACUTE-15/AMP

350 W + 50 W active speaker

15" active speaker bi- amplified - 350W boomer + 50 W HF driver

ref 8674

+ 150 W RMS output

+ Bi-amplified

+ MIC/LINE input

+ Optional mounting bracket : SUP-AC08NO

ACUTE-08/AMP

ACUTE-10/AMP

+ 300 W RMS output

+ Bi-amplified, with a mic/line input

+ Switching Link out/ Mix out controller

ACUTE-12/AMP

+ Power output: 350 W RMS

+ Bi-amplified speakers

+ 2 Entrées micros et 1 ligne avec égaliseur

+ Power output : 350 W RMS

+ 2 input MIC and 1 Line input with equalizer

+ Large frequency response

ACUTE-15/AMP

235

TECHNICAL SPECIFICATIONS

	ACUTE-08/AMP	ACUTE-10/AMP	ACUTE-12/AMP	ACUTE-15/AMP
Ref	8738	9703	8673	8674
Power output	150 W RMS	300 W RMS	350 W RMS	400 W RMS
LF amplifier output	100 W RMS Class G	250 W RMS Class G	300 W RMS Class G	350 W RMS Class G
HF amplifier output	50 W RMS Class AB	50 W RMS Class AB	50 W RMS Class AB	50 W RMS Class AB
Frequency response (-3dB)	70 Hz - 18 kHz	65 Hz - 20 kHz	50 Hz - 20 kHz	50 Hz - 20 kHz
SPL	94 dB (117 max)	95 dB (122 max)	124 dB (127 max)	125.5 dB (128.5 max)
Boomer	8" (21 cm) 120 W RMS / 4 Ω 52 mm voice coil	10" (26 cm) 250 W RMS / 4 Ω 65 mm voice coil	12" (31 cm) 300 W RMS / 4 Ω 75 mm voice coil	15" (38 cm) 350 W RMS / 4 Ω 75 mm voice coil
HF driver	1" 30 W RMS / 8 Ω 1.5" aluminium diaphragm	1" 40 W RMS / 8 Ω 1.5" aluminium diaphragm	1" 50 W RMS / 8 Ω 1.75" titanium diaphragm	Diamètre 1" 50 W RMS / 8 Ω 1.75" titanium diaphragm
24 dB/Oct Filter	3.5 kHz	2.5 kHz	2.2 kHz	2.6 kHz
HxV dispersion horn	90°x 60°	80°x 60°	80°x 60°	80°x 60°
Inputs	1x Mic / Jack 1x Line / XLR	1x Mic / Jack 1x Line / XLR	2x Mic / Jack 1x Line / XLR	2x Mic / Jack 1x Line / XLR
Outputs	1x ligne / XLR	1x Mix ou Link / XLR	Mix / XLR	Mix / XLR
Settings	Mic vol. Line vol.	Mic vol. Line vol.	Bass / Treble +/-10dB Mic 1 vol./ Mic 2 vol. Line vol. / Master vol.	Bass / Treble +/-10dB Mic 1 vol./ Mic 2 vol. Line vol. / Master vol.
Protections	Built-in limiter and thermal captors Frontal ON/OFF LED and rear Signal/Clip LEDs			
Dimensions	435x255x245 mm	557x330x313 mm	615x416x356 mm	740x475x400 mm
Net weight	8 kg	18 kg	25 kg	30 kg

ACCESSORIES

SUP-AC08NO

Wall mount ACUTE 08 • Black version

ref 9598



- Removable fixation bracket
- Uses the M10 rigging points
- Can be vertically or horizontally oriented
- Max load: 10 kg

COV-ACUTE10

Protective cover

For an ACUTE-10 AMP

ref 9713

COV-ACUTE12

Protective cover

For an ACUTE-12 AMP

ref 8699

COV-ACUTE15

Protective cover

For an ACUTE-15 AMP

ref 8700

