



MOJO2200curve

Compact active curve array system with mixer, BT and DSP

Code : H11175

EAN : 3662009022406

Technical data

Column

- Power: 300W RMS - 600W max.
- Nominal impedance: 6 Ohms
- Boomer: 3 X 5" neodymium
- Tweeter: 9 x 1"
- Dispersion: 120° x 70° (HxV)
- Connector: Insert into housing
- Dimensions: 188 x 517 x 243 mm
- Net weight: 8 kg

Subwoofer

- Power: 500W RMS -1000W max.
- Nominal impedance: 4 Ohms
- Boomer: 1 x 12 inches
- Dimensions: 366 x 625 x 541 mm
- Net weight: 27 kg

Complete system

- Frequency response 38 - 18,000Hz
- SPL max. (@1m) 128 dB

Amplifier module.

- Low stage: 1 x 700W RMS / 1400W Max at 6 Ohms
- Mid/high stage 1 x 300W RMS / 600W Max at 4 Ohms

Inputs :

- CH1: 1 x XLR/Line Jack/Microphone Combo
- CH2 : 1 x XLR/Line Mic/Jack Combo
- CH3: 1 x Line Jack
- CH4/5: 1 x RCA L/R line + Bluetooth® input

Input impedances

- Micro 1 & 2 : Balanced 40 KHoms
- Line 1 & 2 : Balanced 10 KHoms
- Line 3 : Balanced 20 KHoms
- Line 4 & 5 : Unbalanced 5 KHoms

Outputs :

- 1 Insert on the top of the housing for the stellite
- 1 x balanced XLR MIX OUT for output to another system
- 2 x XLR LINE OUT balanced for the CH1 and 2 replica

DSP

- 24 bit (1 in 2 out)
- EQ / Presets / low cut / Delay / Bluetooth® TWS

- Adjustment of levels on each channel + Master
- Adjusting the level of the cabinet