

ACUTE-08

120 W RMS ABS monitor

8" passive monitor power handling: 120 W RMS

ref 9596 white version et ref 9595 black version

ACUTE-10

250 W RMS ABS monitor

10" 250 W RMS ABS Speaker - BLACK

ref 9704

ACUTE-12

300 W RMS ABS monitor

12" 300 W RMS ABS Speaker - BLACK

ref 8671

ACUTE-15

300 W RMS ABS monitor

15" 350 W RMS ABS Speaker - BLACK

ref 8672

- + Black or white finishing
- + Use them vertically or horizontally
- + 1.5"
- + Optional mounting bracket available

ACUTE-08

ACUTE-10

- + A very efficient power-to-size ratio
- + 250 W RMS
- + Use it vertically or horizontally

ACUTE-12

- + 300 W RMS
- + An optimized frequency response
- + Weights only 21 kg

ACUTE-15

- + 350 W RMS
- + High-quality basses
- + Very resistant housing, and an optional protective cover

ACCESSORIES

SUP-AC08NO

Wall mount bracket for ACUTE 08

Black version

ref 9598

SUP-AC08WH

Wall mount bracket for ACUTE 08

White version

ref 9599



- Removable mounting bracket
- Fix them directly onto the speakers
- Can be horizontally and vertically adjusted
- Max load: 10 kg

COV-ACUTE10

Protective cover

For a ACUTE-10 AMP

ref 9713

COV-ACUTE12

Protective cover

For a ACUTE-12 AMP

ref 8699

COV-ACUTE15

Protective cover

For a ACUTE-15 AMP

ref 8700



TECHNICAL SPECIFICATIONS

	ACUTE-08	ACUTE-10	ACUTE-12	ACUTE-15
Ref	9596(WH) 9595(NO)	9704	8671	8672
Power output	120 W RMS	250 W RMS	300 W RMS	350 W RMS
Nominal impedance	8 Ω	8 Ω	8 Ω	8 Ω
Frequency response (-3dB)	75 Hz - 18kHz	65 Hz - 20kHz	45 Hz - 18kHz	45 Hz - 18kHz
SPL	94 dB (120 max)	95 dB (122 max)	124 dB (127 max)	125,5 dB (128,5 max)
LF speaker	8" (21 cm) 120 W RMS/ 8 Ω 52mm voice coil	10" (26 cm) 250 W RMS/ 8 Ω 65mm voice coil	12" (31 cm) 300 W RMS/ 8 Ω 75mm voice coil	15" (38 cm) 350 W RMS/ 8 Ω 75mm voice coil
HF driver	1" 30 W RMS/ 8 Ω 1,5" aluminium diaphragm	1" 40 W RMS/ 8 Ω 1,5" aluminium diaphragm	1" 50 W RMS/ 8 Ω 1,75" titanium diaphragm	1" 50 W RMS/ 8 Ω 1,75" titanium diaphragm
12dB/Oct filter	3,5 kHz	2 kHz	2 kHz	1,7 kHz
HxV dispersion horn	90°x60°	80°x60°	80°x60°	80°x60°
Connectors	2x Speakon NL-4x2			
Mounting sockets	5x36mm M6 rigging points	5x36mm M8 rigging points	5x36mm M8 rigging points	5x36mm M8 rigging points
Dimensions	435x255x245 mm	557x330x313 mm	615x416x356 mm	740x475x400 mm
Net weight	7 kg	16 kg	21 kg	25 kg