



# HDMI DA 1:4 - True1

xVision Converter Series



#XVVHDMIDAT1

Professional equipment in mission-critical applications is all about reliability and confidence. So we started with a clean sheet, and built what might soon become your most trustworthy piece of equipment. Introducing the world's first video converters truly designed for the road. Video converters nowadays are used everywhere on professional A/V events, presentations, live shows and tours and often have a critical role. Yet, they are often the weakest link in the signal chain. Low quality connectors, weak enclosure, external consumer-grade power supply, and overall barebones design that all contribute to a generally unreliable piece of equipment. We wanted to change that, so we designed the xVision Video Converters.

## Connections

### Video Input

HDMI 2.0 type A with lock system

### Video Output

4 x HDMI 2.0 type A with lock system  
Individual downscaling per port

## Supported Signals

### Format Support

HDR 4K/2K @ 60 fps (4:2:0 10 bits)  
4K/2K @ 60 fps (4:4:4 8 bits)

**HDCP Compliance**

HDCP 2.2/1.4

**Video Bandwidth**

Single-link 600 MHz (18 Gbps)

**Embedded Audio**

DTS-HD Master Audio, Dolby TrueHD Dolby

**Support**

Digital, DTS, LPCM

**Environmental****Operating Temperature**

0-40° C

**Relative Humidity**

0-90 % non-condensing

**Power Requirements****Power Supply**Built-in power supply PowerCON True1 input  
PowerCON True1 output**Power Consumption**

25W

**Operational Voltage Range**90-250 V  
50-60 Hz**Courtesy Outlet**



Max 10A, same voltage as input

## Physical

### Height

50 mm (1.97 in)

### Depth

180 mm (7.08 in)

### Width

107 mm (4.21 in)

### Weight

1 kg (2.2 lbs)

## In the box

xVision HDMI DA 1:4 (True1)  
AC Mains PowerCon True1 cable (1.5 m, specify plug  
type at ordering)

---

## Certifications



DESIGNED & MANUFACTURED  
IN CANADA 

