

# Product Detail Page



## MMX-602/SW

Number: 20.2230

**Microphone line mixer,**  
6 channels.

- 6 stereo line inputs, 6 balanced mono microphone inputs, switchable
- Adjustable automatic talkover (-12 dB), switchable for channel 1 or channels 1+2
- Balance control for each stereo input channel
- 3-way equalizer
- 12 V phantom power can be switched on additionally
- LED VU meter, peak LED
- Master output and record output
- Output can be switched stereo/mono
- Adjustable headphone output
- 482 mm (19") rack installation, 1 RS

## Technical Facts

Line input, stereo	100 mV/10 k $\Omega$
Microphone input	1 mV/6.6 k $\Omega$
Master output, stereo	1 V/600 $\Omega$
Record output, stereo	310 mV/600 $\Omega$
Headphones, stereo	> 8 $\Omega$
Frequency range	20-20,000 Hz
THD	0.1 %
S/N ratio	62 dB, unweighted
Equalizer, bass	$\pm$ 12 dB/50 Hz
Equalizer, midrange	$\pm$ 12 dB/1 kHz
Equalizer, treble	$\pm$ 12 dB/10 kHz
Power supply	230 V~/50 Hz/12 VA
Admiss. ambient temp.	0-40 $^{\circ}$ C
Dimensions	482x47x208 mm, 1 RS
Weight	2.8 kg
Line input, stereo	6 x RCA L/R
Microphone input	6 x XLR, bal.
Master output, stereo	1 x RCA L/R, 1 x XLR L/R, bal.
Record output, stereo	1 x RCA L/R
Headphones	1 x 6.3 mm jack

