

Product Detail Page



MPX-52PA

Number: 20.2300

2-zone mixer,
for multiroom PA applications.

- 2 independent zones with routing facility of all input channels as desired
- 1 microphone way as announcing channel, balanced, with 3-way equalizer and adjustable automatic talkover
- 4 stereo input channels with stereo line inputs and balanced microphone ways
- Channel 1 additionally with a balanced line input, channels 3 and 4 switchable line/phono
- Signal/peak indication for each channel
- Recessed gain control for each input channel
- Zone outputs, balanced, with 3-way equalizer, LED level indication of the stereo master, balance controls, pre-fader listening (PFL) and mono/stereo selection
- Adjustable headphone output with pre-fader listening (PFL) to the stereo input channels and the zone outputs
- 2 zone outputs for each stereo RCA and XLR L/R, bal.
- 1 record output for each zone (independent of talkover and announcements)
- Connection for gooseneck light GNL-200, GNL-204 or GNL-205



Technical Facts

Mic input	1.5mV
Phono input	3mV
CD input	-
Line input	120mV
Master output	1V
Record output	550mV
Headphones	? 32Ω , stereo
Frequency range	20-20,000Hz
THD	< 0.1%
S/N ratio	71dB, unweighted
Equalizer, bass	±15dB/50Hz
Equalizer, midrange	±12dB/1kHz
Equalizer, treble	±15dB/10kHz
Talkover	level attenuation 20dB max.
Gooseneck light	12V/5W, BNC
Power supply	230V~/50Hz/15VA
Admiss. ambient temp.	0-40 °C
Dimensions	482x138x190mm, 3RS
Weight	4.3kg