



TXA-110

Order No.: 0172420

PRODUCTINFOS

Portable amplifier system,

with integrated adjustable multifrequency receiver unit with UHF PLL technology.

- Robust plastic cabinet of compact size with carrying handle and carrying strap
- Operation via built-in rechargeable lead gel battery 12 V/2.7 Ah (operating time: up to 3 hours) or supplied switch-mode power supply
- Integrated automatic battery charging
- 1 wireless microphone channel with 16 selectable UHF frequencies (863.050-864.925 MHz) and volume control
- 1 microphone input via 6.3 mm jack, 1 line input via 3.5 mm jack, common volume control and tone control
- 1 mix output via 3.5 mm jack
- 9 mm ($\frac{3}{8}$ ") tripod socket
- Supplied with practical protective shoulder bag which can stay on during operation

Licence-free in the EU.

Matching microphone transmitters or pocket transmitters TXA-100HT or TXA-100HSE are available at option.

TECHNICAL SPECIFICATIONS

TXA-110

Rated power (P_{RMS})	36 W
Peak output power	50 W
Frequency range	60-15,000 Hz
Carrier frequency	863.050-864.925 MHz
Operating range	≈ 30 m
Inputs	10 mV (mic), 100 mV (line)
Equalizer, treble	± 8 dB/10 kHz
Power supply	rech. batt. 12 V/2.7 Ah, via encl. power supply
Admiss. ambient temp.	0-40 °C
Dimensions	160 x 210 x 290 mm
Weight	3.15 kg
Connections	1 x 6.3 mm jack (mic), 1 x 3.5 mm jack (line in), 1 x 3.5 mm jack (mix out)