

# BT-PROFILE HD

## B06044

### DESCRIPTION

Very compact, full color LED profile with 4 blades and 25°-50° zoom

### FEATURES

- A very compact but powerful “ALL-IN-1” full color LED profile with:
  - Integrated manual 25° ~ 50° zoom.
  - 4 blade shutter framing system to make sharp beam cuts.
- No more need for separate white and color projectors, BT-PROFILE HD does it all:
  - Perfect WHITE with high CRI > 90Ra and CCT presets
  - Rich COLOR selection with color presets!
- Thanks to the **CCS Color Calibration System** the color differences between different batches is a problem of the past, while this profile also works perfectly together with our existing BT-THEATRE HD2:
  - The same CCT presets for white, ranging from 1800K to 10000K !
  - The same 48 calibrated color presets (according to LEE® / ROSCO® numbering)
- Based on a 150watt 5-color RGBAL LED-cluster (Red, Green, Blue, Amber, Lime)
- Very silent operation with low noise cooling fan and different presets (live, studio, ...)
- DMX-controlled: 6 different channel modes for maximum flexibility
- RDM-functionality for easy remote setup: DMX addressing, channel mode, ...
- Flicker free TV-recordings thanks to the adjustable high LED-refresh rate!
- Four dimmer settings with different behavior & speed.
- Manual control for dimming, colors, CCT & zoom.
- OLED-display to navigate easily through the setup menu!
- In case of DMX failure, you can choose between blackout and freeze mode.
- Lock function to avoid unwanted altering of the settings.
- Lightweight but rugged housing.
- 5pin DMX in/outputs + PowerCON TRUE1 compatible in/outputs for easy daisy chaining.



[www.briteq-lighting.com](http://www.briteq-lighting.com) | <https://www.facebook.com/Briteq>

Beglec NV has the right to change products and specifications with and without notice. Major as well as minor changes can be involved. This leaflet can contain errors, therefore we advice to consult your local dealer to ensure that actual features and specifications match your requirements. Copyright © 2022 by BEGLEC NV. All rights reserved.



## TECHNICAL SPECIFICATIONS

<b>General : Dimensions (cm)</b>	22.4 x 19.1 x 56.8 (b x h x d)
<b>General : Weight (kg)</b>	3.2
<b>General : Powerinput</b>	AC 100 - 240V, 50/60Hz
<b>General : Energy Label</b>	No
<b>General : Power consumption W</b>	170
<b>General : Color</b>	black
<b>General : Display</b>	OLED
<b>General : Fixation</b>	optional standard clamp
<b>General : IP rating</b>	indoor
<b>Control : Modes</b>	standalone fixed, standalone automatic, manual, DMX, DMX Master/Slave
<b>Control : Protocol</b>	DMX, RDM
<b>Control : manual</b>	Yes
<b>Control : Master/Slave</b>	Yes
<b>Control : SMART-DMX</b>	No
<b>Control : Standalone</b>	automatic, fixed
<b>Control : programmable</b>	Yes
<b>Control : upgradable software</b>	No
<b>Control : maximum DMX channels</b>	18
<b>Light : lamp socket</b>	none
<b>Light : Lux</b>	1098 @5m (beam 25°)
<b>Light : lumen</b>	4088
<b>Light : lamp</b>	LED
<b>Light : CRI</b>	90
<b>Light : colors</b>	Red, Green, Blue, Amber, Lime, RGBAL
<b>Light : mix colors</b>	Yes
<b>Light : functions</b>	manual focus, manual zoom
<b>Light : min. beam angle (°)</b>	25
<b>Light : max. beam angle (°)</b>	50
<b>Light : max. refresh rate (kHz)</b>	25
<b>Connections : input</b>	5 pin XLR, PowerCon® TRUE1 or compatible
<b>Connections : output</b>	5 pin XLR, PowerCon® TRUE1 or compatible
<b>Brand</b>	BRITEQ
<b>EANCode</b>	5420025660440



## YOUR DEALER



[www.briteq-lighting.com](http://www.briteq-lighting.com) | <https://www.facebook.com/Briteq>

Beglec NV has the right to change products and specifications with and without notice. Major as well as minor changes can be involved. This leaflet can contain errors, therefore we advice to consult your local dealer to ensure that actual features and specifications match your requirements. Copyright © 2022 by BEGLEC NV. All rights reserved.