



Visit product page



IOS 15A DSP

L005671

Professional plywood active speaker 15 inch with LCD screen and multiple DSP, German Engineering class D amplifier, 500W (LF) + 500W (HF), 1000w RMS, 1.35" HF drive, 15" woofer 2,5" VC, flypoints, top handle and stage monitor feature.

TECHNICAL DETAILS

Technical Specifications

2 way, bi-amp active vented design.

Power output: 1000W.

German Engineering Class D amplifier + switching power supply.

Frequency Response: 45 - 20 kHz.

Max. Output SPL: 129 dB.

Impedance: 4 Ohm.

Inputs: 1x XLR/1/4", 1x XLR.

Outputs: 1x XLR.

Woofer 15" x1.

1,35" driver x1.

Directivity: 90° H x 60° V.

Crossover point: 1.6 kHz.

Power input: 220 / 240 Volt AC, 50 / 60 Hz.

LCD Screen & multiple DSP.

15 mm PLY cabinet.

Flypoints: M10

Pole Socket: Ø35 mm.

Dimensions: 73 x 44 x 43,9 cm.

Gross Weight: 26.3 Kg.

Packing Details

Dimensions: 56 x 56 x 85 cm

Weight: 29 kg

PHOTOS



PRODUCT VIDEO




ACCESSORIES



iCover IOS15

Cover for IOS 15



www.fos-lighting.eu

