



Visit product page



KEA SYSTEM

L005697

Portable PA column system, lightweight and feature packed. speaker 2 x 4" HF, 1x 10" SUB, 123 dB SPL, 255W (sub)+60w (sat), German Engineering Class D amplifier, Frequency response 50-20kHz, internal 6ch mixer with Echo & Delay Effects and bluetooth.

TECHNICAL DETAILS

Technical Specifications

Inputs: 4x XLR/TRS combo balance, 1x TS/RCA stereo, 1x 3.5 mm (AUX) Bluetooth.

Output: 1x TS Stereo Monitor out.

IEC power connection.

Power Voltage: 220 / 240 Volt AC, 50/60 Hz.

Total Power: 370 Watt RMS.

Soft limit.

System frequency: 50 Hz - 20 kHz, +/- 3 dB.

Active Subwoofer:

Driver: 1x 10".

Power: 250 Watt RMS.

Frequency range: 50 Hz - 160 Hz.

Max. SPL: 123 dB.

Plastic cabinet.

Dimensions: 45.8 x 35 x 40,7 cm.

Weight: 14 Kg.

Satellite:

Drivers: woofer 1x 4.75", tweeter 1x 1".
Power: Mode 1: 60 Watt RMS, Mode 2: 120 Watt RMS.
Frequency Range: 155 Hz - 20 kHz.
Max SPL: Mode 1: 125 dB, Mode 2: 130 dB.
Dimensions: 22,7 x 14 x 15.5 cm.
Weight: 4 Kg.

Packing Details

Dimensions: 49 x 43 x 52 cm
Weight: 20 Kg

PHOTOS



PRODUCT VIDEO



ACCESSORIES



iCover Kea System
Cover for Kea System



www.fos-lighting.eu

