



Visit product page



TILOS L SUB

L005682

Professional plywood active vented subwoofer 2 X10 inch for the Tilos Column system, 500w Rms, 121 dB Spl, German Engineering D class amplifier, multiple DSP ,XLR input, sat mode select, Frequency response 50-200 Hz.

TECHNICAL DETAILS

Technical Specifications

Active vented subwoofer.

Inputs: XLR/TRS combo jack.

Output: XLR balanced line, XLR LINK, SAT Out.

250 Watt RMS (subwoofer) & 250 Watt RMS (satelite).

Subwoofer volume control, +4 / -10 dB sensitivity switch.

Power Input: 115 / 230 Volt AC, 50 / 60 Hz switchable.

German Engineering Class D amplifier + switching power supply.

Sat Mode selection.

Power / clip indicator.

DSP effect processor.

Excellent compressor.

Frequency response: 50 - 200 Hz.

Max. output SPL: 118 dB.

Driver: 10" subwoofer, 2,5" VC 45 oZ.

PLY cabinet with black painted finish.

1,2 mm steel mesh.

Packing Dimensions: 61,5 x 45,5 x 76 cm.

Gross Weight: 27,5 Kg.

PHOTOS




PRODUCT VIDEO



ACCESSORIES



iCover Tilos L
Cover for Tilos L



www.fos-lighting.eu

