



Visit product page



CLIMATE IP5 -PEARL

L005757

High Quality public address 2 way speaker, dust-proof and waterproof IP55, 100/70V and 8 \bar{U} , U type steel bracket included, ideal for out door installations, max input 60W/100V , 160W/8 \bar{U} , SPL 90 dB, 5?? Woofer + 1?? Tweeter, rugged HIPS white housing.

TECHNICAL DETAILS

Technical Specifications

Rated Input: 40W@100V; 80W@8 \bar{U}

Max Input: 60W@100V; 160W@8 \bar{U}

High Impedance: 125 \bar{U} , 250 \bar{U} , 500 \bar{U} , 1k \bar{U} , 2k \bar{U}

Power Taps: 100V: 40W, 20W, 10W, 5W; 70V: 40W, 20W, 10W, 5W, 2.5W

SPL (1W / 1m): 90dB

MAX SPL (Rated / 1m): 106dB@100/70V; 109dB@8 \bar{U}

Frequency Response(-10dB): 70Hz~20kHz

Crossover Slope: 12dB / Octave

Dispersion (4kHz / 1kHz): 125° / 190°

Power Selecting Way: Rotating Selection Switch

Material: Housing: HIPS; Grille: Steel

Temperature / Humidity: -30°C ~ 60°C; <95%

Water Protection: IEC529 IP55

Speaker Component: 5" Woofer + 1" Tweeter

Dimensions: 196(W) x 295(H) x 157(D)

Weight: 3.6kg

Mounting: U Type Mounting Bracket Or Optional Other Bracket

Shipping Weight: 17kg, 4pcs

Shipping Dimensions: 0.0718CBM, 50 x 41 x 35 cm, 4pcs

PHOTOS



PRODUCT VIDEO





www.fos-lighting.eu

