



Visit product page



FOS F-6 GO

L005927

Moving Outdoor IP 65 Washer, 44 led 10 watt RGBW 4in1, Tilt (Degrees): 185°, 16Bit Tilt resolution, 35° lens optics, IP65 XLR and True powercon connectors, USITT DMX-512, RDM, Auto Run Effects, Die-casting Aluminum, 10kg

TECHNICAL DETAILS

Features

Moving LED washer based on 44x RGBW LEDs, 10 Watt each.

Tilt movement 8 & 16 bit, 185° angle.

0 - 100% dimming with 5 dimmer modes.

Colour effects with adjustable speed.

Technical Specifications

Power Supply: 100/240 Volt AC, 50/60 Hz.

Power Consumption: 400 Watt Maximum.

Environmental operating temperature: -30°C to + 50°C.

Omega brackets for truss installation.

Dimensions: 482 x 178 x 243 mm (L x W x H - with head horizontal-).

Net weight: 10 Kg.

Gross weight: 12,5 Kg.

PHOTOS



PRODUCT VIDEO



ACCESSORIES



FC-TP-PDC-5

Professional
TruePowercon/ DMX cable
5 meter.



FC-TP-PDC-3

Professional
TruePowercon/ DMX cable
3 meter.



FC-TP-PDC-1.5

Professional
TruePowercon/ DMX cable
1.5 meter.



**FOS Case Cyclone PRO/F-6
GO**

Flight case with wheels for
4 pcs Cyclone PRO or F



www.fos-lighting.eu

