

BT-THEATRE 400TW

B06045

DESCRIPTION

Powerful 400W LED theater / TV Fresnel with tunable white ranging from 2800K to 6000K, combined with exceptional photometric / price ratio and good light output!

FEATURES

- Powerful 400W LED theater Fresnel with **adjustable CCT**.
- Dual LED (200W 2800K + 200W 6000K) for tunable white with CCT ranging from 2800K to 6000K !
- The perfect all-round projector for TV-work, theatre, rental, exhibition booths!
- Exceptional photometric / price performance: CRI/Ra > 96, TLCI > 98, CQS > 96, Rf > 94, Rg > 100 (@3000K).
- DMX-controlled, motorized beam angle adjustment: 11° ~ 56° (field angle: 20° ~ 67°).
- Manual CCT presets while used in standalone: 2800K, 3000K, 3200K, 4000K, 4300K, 5600K, 6000K.
- Color frame for use of color filters and eight-leaf barndoor included.
- No more heavy and expensive dimmer packs needed!
- Very silent operation: temperature controlled, low noise cooling fan.
- LCD-display to navigate easily through the setup menu!
- Manual or DMX-controlled: 6 different channel modes (8bit & 16bit dimming) for maximum flexibility.
- Can be used 1 channel DMX mode, with CCT-preset of your choice.
- Prepared for wireless DMX: just plug-in an optional WTR-DMX DONGLE !
- Flicker free TV-recordings thanks to adjustable LED refresh rate: 600 Hz to 4800 Hz!
- Manual dimming & zoom/focus control: easy projector alignment on the stage + use on exhibition booths.
- Selectable lamp behavior: halogen lamp (slow) or led (fast).
- Four dimmer curves: linear, square, inverse square, S-curve.
- In case of DMX failure, you can choose between manual, blackout and freeze mode.
- RDM-functionality for easy remote setup & monitoring: DMX addressing, channel mode, temperature, ...
- Lock function to avoid unwanted altering of the settings.
- Default factory settings + user settings can be saved/loaded.
- 3 & 5pin DMX in/outputs + PowerCON® compatible in/outputs for easy daisy chaining.



CCT 2800K — SEAMLESS CCT-CONTROL —> CCT 6000K




www.briteq-lighting.com | <https://www.facebook.com/Briteq>

Beglec NV has the right to change products and specifications with and without notice. Major as well as minor changes can be involved. This leaflet can contain errors, therefore we advice to consult your local dealer to ensure that actual features and specifications match your requirements. Copyright © 2022 by BEGLEC NV. All rights reserved.






TECHNICAL SPECIFICATIONS

General : Dimensions (cm)	See drawing
General : Weight (kg)	8.25
General : Powerinput	AC 100 - 240V, 50/60Hz
General : Energy Label	No
General : Power consumption W	210
General : Color	black
General : Display	LCD
General : Fixation	M12
General : IP rating	indoor
Control : Modes	standalone fixed, manual, DMX
Control : Protocol	DMX, Wireless DMX, RDM
Control : programmable	No
Control : upgradable software	Yes
Control : minimum DMX channels	1
Control : maximum DMX channels	6
Light : lamp socket	No
Light : Lux	5280 (@5m beam 11°)
Light : lamp	COB
Light : min. color temperature (K)	2800
Light : max. color temperature (K)	6000
Light : CRI	97
Light : colors	Cold white, Warm white
Light : mix colors	Yes
Light : functions	manual focus, manual zoom
Light : min. beam angle (°)	11
Light : max. beam angle (°)	56
Light : max. refresh rate (kHz)	4.8
Connections : input	3 pin XLR, 5 pin XLR, wireless DMX optional, usb, PowerCon® or compatible
Connections : output	3 pin XLR, 5 pin XLR, usb, PowerCon® or compatible
Brand	BRITEQ
EANCode	5420025660457



CCT-setting: 3000K



www.briteq-lighting.com | <https://www.facebook.com/Briteq>

Beglec NV has the right to change products and specifications with and without notice. Major as well as minor changes can be involved. This leaflet can contain errors, therefore we advice to consult your local dealer to ensure that actual features and specifications match your requirements. Copyright © 2022 by BEGLEC NV. All rights reserved.