



Visit product page



## FOS ODEUM WASH

L007408

Professional Wash moving head for high-performance applications, low noise operation, High CRI 95, linear CTO 2.200-10.000K , 19 led 25-watt RGB+Warm White, motorized zoom 10-60 degrees, 4 dimmer curves, 14 and 27 ch DMX modes, 3 led pixel rings with presets and color macros, powercon in/out, LCD display , 9.5kg.

### TECHNICAL DETAILS

#### Product Description

Lightweight wash moving head, with motorized zoom, OSRAM RGBW LEDs, Warm White, offering high CRI, and a variety of color temperatures, and low noise operation. Professional Wash moving head for high-performance applications, low noise operation, High CRI 95, linear CTO 2.200-10.000K , 19 led 25-watt RGB+Warm White, motorized zoom 10-60 degrees, 4 dimmer curves, 14 and 27 ch DMX modes, 3 led pixel rings with presets and color macros, power con in/out, LCD display

#### Light Source / Optics

Based on 19x 25-watt OSRAM LED modules, 4 in 1.

High CRI>95.

Motorized Zoom ranges from 10 to 60 degrees.

Color temperature ranges from 2500 to 10000K.

#### Effects

RGBW color mixing.

3-pixel control (outer, inner rings, and center LED).

Linear dimming and variable strobe up to 25Hz.

4 different dimmer curves.

Pan & Tilt movement (Pan 540 & Tilt 270 degrees, 16bit).

## Technical Specifications

Power input: AC100/240 Volt, 50/60 Hz

Power consumption: 430 watts (max).

IP20 for indoor use only.

Silent fan, with less than 40 dB noise level.

Average LED lifespan: 50,000 hours.

Automatic repositioning of the yoke.

RDM compatible.

3-phase motors for precise and fast Pan/Tilt movements.

Blue/White LCD for accessing the options menu.

Daisy chain of maximum 9 fixtures (at 230V), with PowerCon input/output connectors.

Fixture dimensions: 350 x 200 x 400 mm.

Net Weight: 9,5 Kgs.

Packing size: 47 x 26.5 x 56.5 cm

Gross Weight: 11 Kgs.

## PHOTOS



## PRODUCT VIDEO



## ACCESSORIES



**FOS Case Odeum Wash**

Flight case with wheels for 4 pcs Odeum Wash.



**FOS Folded Super Clamp 100**

Self lock clamp with folded operation for reduce t



**FOS CLAMP 100**

Professional clamp for fixtures lifting weight 100



**FC-PDC-1.5**

Professional PowerCon / DMX cable 1.5 meter,



**FC-PDC-3**

Professional PowerCon / DMX cable 3 meter,



**FC-PDC-5**

Professional PowerCon / DMX cable 5 meter,

