



Visit product page



IOS STAGE MONITOR 15

L007501

Coaxial Stage monitor, 350 watt RMS, class D Amplifier, woofer 15inch 2.5VC , driver 1.35-inch Ferrite CD, signal processing by DSP, max output SPL 124 dB, sensitivity 96dB, plywood painted cabinet, pole mount 35mm, XLR and power con in/out, 20kg.

TECHNICAL DETAILS

Technical Specifications

Inputs: Bal XLR/TRS 6,35 mm

Outputs: Balanced XLR

Power Output: 350 RMS

Power Input: 110/220 Volt, 60/50 Hz Switchable.

Features: BI-AMP coaxial speaker LF: Class-D HF: Class-AB.

Signal Processing: DSP

DSP Parameter: Music/Flat/Low Cut/Stage/Vocal

Frequency Range: 55 Hz - 20 kHz.

Max output SPL: 124 dB.

Sensitivity: 96 dB.

Woofer: 15" ; 2,5" VC, 43 Oz.

Driver: 1,35" Ferrite CD

Cabinet: PLY painted cabinet.

Fuse: T3.15AL / 250 Volt.

Pole mount: 35 mm stand pole.

Dimensions / Weight: 49,5 x 40,6 x 60,9 cm / 20,5 Kgs

PHOTOS

