



Visit product page



IOS STAGE MONITOR 12

L007500

Coaxial Stage monitor, 350 watt RMS, class D Amplifier, woofer 12inch2.5 VC, driver 1.35 inch Ferrite CD, signal processing by DSP, max output SPL 123 dB, sensitivity 95 dB, plywood painted cabinet, pole mount 35mm, XLR and power con in/out, 16kg.

TECHNICAL DETAILS

Technical Specifications

Inputs: Bal XLR/TRS 6,35 mm

Outputs: Balanced XLR

Power Output: 350 RMS

Power Input: 110/220 Volt, 60/50 Hz Switchable.

Features: BI-AMP coaxial speaker LF: Class-D HF: Class-AB.

Signal Processing: DSP

DSP Parameter: Music/Flat/Low Cut/Stage/Vocal

Frequency Range: 65 Hz - 20 kHz.

Max output SPL: 123 dB.

Sensitivity: 95 dB.

Woofer: 12" ; 2,5" VC, 43 Oz.

Driver: 1,35" Ferrite CD

Cabinet: PLY painted cabinet.

Fuse: T3.15AL / 250 Volt.

Pole mount: 35 mm stand pole.

Dimensions / Weight: 44,9 x 33,7 x 50,8 cm / 16 Kgs

PHOTOS

