

Installation speakers series

# S SERIES

The very best compact speakers can offer.

The S series elected their worthy heirs. Thought out to be as efficient in nomad than in permanent installations, the S series speakers offer a tremendous power (from 100 to 250 W RMS) and now fully benefit from a new plywood cabinet, meaning they are consequently lighter and way more resistant.

Mounting bracket sold separately

- + New plywood cabinet
- + A whole range of wall mount accessories available
- + Magnificent black or white finishing



They are incredibly robust and will probably outlive many other speakers, and fit any kind of installation thanks to their brand new and very useful mounting bracket. But it is not over yet: two finishings for an even better adaptability, and an extremely clear, precise and balanced output, should it be playing instruments or voice.

+ Power output: 100 W RMS / 200 W peak

+ Very adaptable, compact format

+ Black or white finishing and mounting accessories available

## S6

Satellite 100W RMS

S6 - Black version  
ref 9689

S6W - White version  
ref 9690

### TECHNICAL SPECIFICATIONS

- Plywood enclosure
- Finishing :
  - Black granite powder paint
  - Integral steel grill protection
  - 1 rear cut-away handle
- Frequency response (-3 dB) : 80 Hz - 20 kHz
- Power output : 100 W RMS / 200 W peak
- Impedance : 8 Ω
- Sensitivity 1 W/1 m : 93 dB / 118 dB peak
- Boomer : 6.5" die cast aluminium frame with 45 mm voice coil
- HF driver : 1" driver with 25 mm voice coil
- Horizontal dispersion : 90°
- Vertical dispersion : 60°
- Internal passive filter : cutoff frequency 2000 Hz
- Connectors : Speakon x 2 (1+1- full range)
- Mounting socket for spacer pole
- Dimensions (L x W x H) : 222 x 365 x 205 mm
- Net weight : 6.5 kg

### ACCESSORIES

Mounting brackets



**SUPS6/NO**

For S6 satellite - black  
ref 9705

**SUPS6/WH**

For S6 satellite - white  
ref 9706

+ Power output: 150 W RMS / 300 W peak

+ 1 monitor-specific angle

+ Black or white finishing and mounting accessories available

## S8

Satellite 150 W RMS

S8 - Black version  
ref 9691

S8W - White version  
ref 9692

### TECHNICAL SPECIFICATIONS

- Plywood enclosure with a monitor-specific angle
- Finishing :
  - Black granite powder paint
  - Integral steel grill protection
  - 1 cut-away handle
- Frequency response (-3 dB) : 80 Hz - 19 kHz
- Power output : 150 W RMS / 300 W peak
- Impedance : 8 Ω
- Sensitivity 1 W/1 m : 94 dB / 121 dB peak
- Boomer : 8" die cast aluminium frame with 50 mm voice coil
- HF driver : 1" driver with 44 mm voice coil
- Horizontal dispersion : 50 or 100°
- Vertical dispersion : 55°
- Internal passive filter : cut-off frequency 2100 Hz
- Connectors : Speakon x 2 (1+1- full range)
- Mounting socket for spacer pole
- Dimensions (L x W x H) : 280 x 420 x 233 mm
- Net weight : 10 kg

**SUPS8/NO**

For S8 satellite - black  
ref 9707

**SUPS8/WH**

For S8 satellite - white  
ref 9708

+ Power output: 250 W RMS

+ Astounding rendering

+ Black or white finishing and mounting accessories available

## S10

Satellite 250 W RMS

S10 - Black version  
ref 9693

S10W - White version  
ref 9694

### TECHNICAL SPECIFICATIONS

- Plywood enclosure with a monitor-specific angle
- Finishing :
  - Black granite powder paint
  - Integral steel grill protection
  - 1 cut-away handle
- Frequency response (-3 dB) : 75 Hz - 19 kHz
- Power output: 250 W RMS / 500 W peak
- Impedance : 8 Ω
- Sensitivity 1 W/1 m : 96 dB / 126 dB peak
- HF driver : 10" die cast aluminium frame with 65 mm voice coil
- HF driver : 1" driver with 44 mm voice coil
- Horizontal dispersion : 50 or 100°
- Vertical dispersion : 55°
- Internal passive filter : cut-off frequency 2600 Hz
- Connectors : Speakon x 2 (1+1- full range)
- Mounting socket for spacer pole
- Dimensions (L x W x H) : 320 x 530 x 280 mm
- Net weight : 14.5 kg

**SUPS10/NO**

For S10 satellite - black  
ref 9709

**SUPS10/WH**

For S10 satellite - white  
ref 9710