

Microphone Accessories

PROFESSIONAL SOUND EQUIPMENT

MP100

Microphone Adapter

The MP100 by AUDAC is a simple to use power module for phantom power type condenser microphones; specially for headset and lavalier microphones. The MP100 features a mini-XLR input connector and XLR output connector.



APM

Base for paging microphone

The APM microphone base is designed to use standard gooseneck microphones on any amplifier equipped with microphone inputs.

On top, there's a female XLR connector to mount the gooseneck microphone and at the back, there's a male XLR connector to connect the microphone cable.

The APM microphone base features the same design as the APM paging microphones to fully blend in with the other equipment.



APT20

Phantom Power Supply

The AUDAC APT20 is a mains (main?? supply unit for microphone power supply of 48 V for two condenser microphones. It features XLR connectors for in- and output.



HM150

Vocal Microphone

The AUDAC HM150 is a sturdy CB type hand-held paging microphone with an easy to use Push to talk switch at the side.

This omnidirectional dynamic microphone is designed for close talking applications and is ideal for paging messages to all zones. The built-in 2-pole non latching switch activates the microphone when pressed. Removing pressure from the switch will automatically turn off the microphone. A metal wall mountingclip is provided with the microphone.



AUDAC
www.audac.eu

About Audac :

AUDAC provides a complete range of audio equipment such as amplifiers, loudspeakers, microphones, conference microphones and much more.



Microphone Accessories

PROFESSIONAL SOUND EQUIPMENT

PRODUCT FEATURES :			
	APM	MP100	APT20
Operating Voltage	n/a	n/a	24 V DC
Phantom Power	n/a	n/a	18 V DC
Current consumption	n/a	n/a	tba
Construction	Steel	Metal	Aluminum
Connector	2 x Xlr	XLR - mini XLR	XLR
Dimensions (WxHxD)	120 x 192 x 50 mm	19 x 86 x 19 mm	44 x 110 x 160 mm
Weight	0,500 Kg	70 g	tba
Colour	Grey RAL7016	Black	

PRODUCT FEATURES :	
	HM150
Type	Dynamic
Polar Pattern	Cardioid
Impedance	300 Ohm
Frequency Response	50 Hz - 18 kHz
Sensitivity	-75 dB ± 3dB
Signal to noise ratio	n/a
Maximum Input SPL	n/a
Operating Voltage	n/a
Phantom Power	n/a
Current consumption	n/a
Voice coil	Copper
Construction	On/Off switch
Connector	XLR
Length Connection Cable	5 m
Dimensions (WxHxD)	49 x 182 x 49 mm
Weight	0,300 Kg
Colour	Grey
Accessories	Microphone clamp
	Microphone cable
Option	MC50 Windscreen

AUDAC
www.audac.eu

 **CE** approved product

For a period of 2 years, starting from the original date of purchase, Audac products are covered against defects in workmanship or materials. The defective item will be repaired or replaced at the option of Audac, with no charge for materials or labour. You have to adequately pack up and dispatch the item prepaid to a Audac authorized distributor/service centre. Unauthorized repair shall void the warranty. Cosmetics and finish are not covered by this Audac warranty. The warranty is also voided if, in Audac's opinion, the items have failed due to user abuse, accidents, modifications or any type of misuse.

