

Product Detail Page



PA-6600

Number: 17.2390

6-zone mono PA mixing amplifiers

- 1 x 240W_{RMS} (PA-6240)
- 1 x 480W_{RMS} (PA-6480)
- 1 x 600W_{RMS} (PA-6600)
- 6 zones, can be controlled individually
- Chime, continuous sound and wailing sound, automatic mute, 2-tone chime or 4-tone chime (selectable)
- Bass, treble and master controls, level display via LEDs, regulated fan
- Insertions for various functions are available at option
- 17V phantom power for electret microphones
- Connection for zone paging microphone PA-6000RC
- 1 insertion compartment at the front for automatic alarm message insertion PA-1120DM, a tuner insertion or a CD player insertion (all available at option)
- 3 insertion facilities at the rear side for optional modules with the following features:
 - PA-6FD: fault detection
 - PA-6FM: fault monitoring
 - PA-6FR: anti-feedback
- Mains operation and 24V emergency power operation
- Removable mounting brackets



Technical Facts

General information

Output power	600W _{RMS}
	850W _{MAX}

Inputs

Mic/line 1-3	2.5mV/5k Ω , 0.3V/5k Ω
Line 4-5	0.3V/15k Ω
Preamplifier	0.775V/10k Ω

Outputs

Speakers	100V/70V
Preamplifier	0.775V/100 Ω
Record	0.775V/3k Ω
Frequency range	55-16,000Hz

Tone control

Bass	\pm 10dB/100Hz
Treble	\pm 10dB/10kHz

S/N ratio

Mic	> 70dB, A-weighted
Line	> 80dB, A-weighted
THD	< 1%
Admiss. ambient temp.	0-40 °C

Power supply	230V~/50Hz/1,700VA, 24V = /50A
---------------------	-----------------------------------

Dimensions	430x133x352mm, 3RS
-------------------	--------------------

Weight	20kg
---------------	------

Inputs

Mic/line	3 x 6.3mm/XLR (Combo)
Line	2 x RCA L/R
Zone paging microphone	2 x RJ-45, optional
Push-to-talk microphone	1 x 7-pole DIN
Telephone system	screw terminals



Ext. amplifier	1 x 6.3mm jack
Outputs	
Mom. push-button for chime	-
1 x preamplifier	1 x 6.3mm jack
Speakers	screw terminals
Record	1 x RCA L/R
Power supply	
230V~	3-pin IEC jack
24V DC current	screw terminals

