



Visit product page



FOS CYCLONE RGB II

L004667

Pixel RGB Strobe, 960 leds SMD, 8 Pixel Sections, Beam Angle: 120 degrees, Strobe frequency: 1~30HZ, 3 DMX modes CH03, CH09, and CH24 channels, powercon input/output, IP20, 6 kg.

TECHNICAL DETAILS

Light Source/Optics

Light Source: 960x 0,4 W RGB LED
120 degree Beam Angle
50,000 Hour Average LED Life

Effects

RGB Color Mixing.
8 independent LED control sections.
Built in chases with variable speed
Linear dimming.

Control

3 DMX control modes: 3, 9* & 24 channels.

*Strobe function is available in 9 channel mode. 3 channel mode controls RGB sections as one, and 24 channel mode, controls 8 sections of RGB independently.

3pin XLR DMX in/out

Technical Specifications

Power input: 100 / 240 Volt AC, 50/60 Hz.


Maximum power consumption: 240 Watt.

Metal black housing.
IP 20, for indoor use only.
Packing dimensions: 49 x 28 x 16 cm.
Fixture dimensions: 46 x 24 x 10,5 cm.
Weight: 5,3 Kgs.
Gross Weight: 6 Kgs.

PHOTOS



PRODUCT VIDEO



www.fos-lighting.eu

