



Visit product page



FOS HELIX PRO

L005316

Led Wash moving head with 19 Led 15 watt, zoom 4 - 60 degrees, Pixel Patterning Macros , Bi Directional Rotating Front Lens, RGBW Color mixing and independent pixel control. Kaleidoscopic effect with the rotation of the front lens. Strobe effects with adjustable speed.

TECHNICAL DETAILS

Light Source / Optics

19x 15 Watt 4 in 1 LEDs.
RGBW Color mixing and independent pixel control.
Motorized zoom with range from 4 to 60 degrees.

Effects

RGBW color mixing.
Beam and Wash light projections
Kaleidoscopic effect with the rotation of the front lens.
Strobe effects with adjustable speed.
Pixel control in the extended DMX control modes.
Pre-programmed macros and LED patterns.

Control

DMX512, Auto, Manual, Master Slave & Music control modes.
Pan 540 & Tilt 270 degrees with 16bit movement resolution.

Dimensions / Installation Details

Power Supply: 100 / 240 Volt AC, 50/60 Hz.

Power Consumption: 450 Watt.

Noise level at 1 meter: 45 dB.

IP20 (for indoor use only).

Dimensions: 415 x 275 x 425 mm

Carton Package: 530 x 420 x 510 mm

Net Weight: 14,95 Kg.

Gross Weight: 18,1 Kg.

Photometric Data

Measuring distance: 5 Meters

Full On (RGBW) minimum zoom

Illuminance (lx): 13830

Flicker Frequency (Hz): 70

Flicker(%): 15

Full On (RGBW) maximum zoom

Illuminance (lx): 638

Flicker Frequency (Hz): 205

Flicker(%): 3

White minimum zoom

Color Temperature (K): 6849

Illuminance (lx): 6047

CRI (Ra): 72

TLCI (Qa): 49.1

Flicker Frequency (Hz): 262

Flicker(%): 17

White maximum zoom

Color Temperature (K): 7731

Illuminance (lx): 271

CRI (Ra): 73

TLCI (Qa): 49.4

Flicker Frequency (Hz): 115

Flicker(%): 5

For data of every color, see the full documentation on Documents tab.

PHOTOS



PRODUCT VIDEO



ACCESSORIES



FOS Double Case Helix

Double Case with Wheels
for 2 pcs Helix.



www.fos-lighting.eu

