



Visit product page



IOS 10A DSP

L005669

Professional plywood active speaker 10 inch with LCD screen and multiple DSP, German Engineering class D amplifier, 350W (LF) + 350W (HF), 700w RMS, 1.35 HF drive, 10" woofer 2" VC, flypoints, top handle and stage monitor feature.

TECHNICAL DETAILS

Technical Specifications

2 way, bi-amp active vented design.

Power output: 700W.

German Engineering Class D amplifier + switching power supply.

Frequency Response: 60 - 20 kHz.

Max. Output SPL: 126 dB.

Impedance: 4 Ohm.

Input SPL: -10 dBV.

Inputs: 1x XLR/1/4"

Outputs: 1x XLR.

Woofer 10" x1.

1,35" driver x1.

Directivity: 90° H x 60° V.

Crossover point: 1.9 kHz.

Power input: 220 / 240 Volt AC, 50 / 60 Hz.

LCD screen & multiple DSP.

15 mm PLY cabinet.

Flypoints: M8

Pole Socket: Ø35 mm.

Dimensions: 56 x 31 x 32,5 cm.

Gross Weight: 15.6 Kg.

Packing Details

Dimensions: 41 x 41 x 64 cm

Weight: 18 kg

PHOTOS



PRODUCT VIDEO




ACCESSORIES



iCover IOS10

Cover for IOS 10



www.fos-lighting.eu

