

MASK8F-W / MASK8F-BL HIFI PRO DESIGN SPEAKER



APart MASK loudspeakers have been designed for the contractor market and supply you with a clear sound, from back ground music up to "dance level" music.

MASK8F has a unique and very stylish innovative design. The curved fine metal grill together with the shape of the wooden delta cabinet gives MASK8F a different, yet inconspicuous look.

MASK8F has a very powerful 8" coated paper cone woofer. Together with the Ferro-fluid cooled silk dome tweeter on a Waveguide horn, this results in a high SPL, an ultra low distortion and a sound that comes close to studio monitor quality!

MASK8F loudspeakers are full range loudspeakers, which means they are especially designed to give a full sound without using subwoofers. Its wide frequency range makes sure every note, starting from the bass over the clean middle range to the crystal clear highs, reaches your ears with an astonishing clarity.

The build-in Auto-Reset 3-step Protection Guard together with the quality components make MASK8F a fail-safe loudspeaker, even at high power loads!

MASK8F is delivered with a metal U-Mounting Bracket. After mounting the bracket on the wall, the sleeve in the bracket makes it quite easy and safe to fix the MASK8F loudspeakers, even in uncomfortable positions. The MASK8F cabinet has several thread mounting points tapped at the back, the top and side of the cabinet. This way the cabinet can be rigged or mounting clamps can be used. An extra contractor advantage! MASK8F-BL also has a pole mount adapter in its bottom. This adapter makes it possible to mount the speaker on top of a standard 35mm pole such as the APart STFLOOR, STSUB and STT. Please note this feature is not available on MASK8F-W.

MASK8F is available in black (Ref; MASK8F-BL) and white (Ref; MASK8F-W). MASK8F loudspeakers can be painted in any RAL color (Ref; PAINT-CAB8) Please note that the minimum order quantity for PAINT-CAB8 is 12 pieces.

TECHNICAL SPECIFICATIONS

Type :	2-way HiFi Pro, bass reflex
Cabinet :	MDF Wood
Woofer :	8" HD Type
Tweeter :	1" HD silk dome on Waveguide
Impedance :	8 Ohm
RMS Power	8 ohm
AES Rated :	230 watt
Music - Program :	300 Watts
Dynamic Peak (low-cut) :	600 Watts
Protection :	Auto-Reset 3-step Protection Guard
SPL 1 watt/1M :	93 dB
SPL Max peak :	124 dB
Frequency response:	50 Hz - 25 KHz
Connector :	Speakon / Speakon
Dispersion :	100° H x 70° V Rotatable Horn
IP rating :	Indoor use only (IP40)
Mounting points	
Back :	2
Top / Bottom :	1 / 1
Left / Right :	2 / 2
Thread :	M8
Dimensions :	
Weight :	411 x 250 x 250 mm 8.1 Kg