



DYNAMIC WHITE PAR

COMPACT LED FIXTURE COLD WHITE AND WARM WHITE LEDS




The CLF Dynamic White PAR is a compact LED fixture with an extraordinary high light output which contains warm and cold white high power LEDs. The powerful LEDs provide extremely high light output and ensures 'flicker-free' operation when using cameras. The Dynamic White PAR contains specially selected LEDs which provide cold and warm white with a CRI > 90. The powerful LEDs provide extremely bright light output and ensures 'flicker-free' operation for all types of TV and film use. Warm and cold white control between 2,800K and 6,500K and colour mixing can be adjusted in 3 different DMX modes or by using the on-board menu. The fixture contains both powerCON in and out and can be connected with three pins XLR. No fan is installed in the Dynamic White PAR so it is also suitable for silent applications.

The fixture can be placed on the floor or mounted to truss structures by using the unique CLF quicklock system. This hanging system is easy to use and time-saving. The solid housing of the fixture makes it suitable for every rental stock and fixed installations.



CLF DYNAMIC WHITE PAR

- » 25° BEAM ANGLE
- » EXTENSIVE WHITE COLOR TEMPERATURE CONTROL (2,800K – 6,500K, CRI>90)
- » SOLID HOUSING
- » DOUBLE BRACKET FOR FLOOR AND TRUSS MOUNTING
- » 'FLICKER FREE' OPERATION
- » POWERCON IN AND OUT



Height	Eavg,Emax	Angle: 20.40°	Diameter
9.843ft 3m	126.0,193.9fc 1357,2087lx		3.542ft 107.96cm
13.12ft 4m	70.90,109.1fc 763.2,1174lx		4.723ft 143.94cm
16.40ft 5m	45.38,69.81fc 488.4,751.4lx		5.903ft 179.93cm
19.69ft 6m	31.51,48.48fc 339.2,521.8lx		7.084ft 215.91cm
22.97ft 7m	23.15,35.62fc 249.2,383.4lx		8.2648ft 251.90cm

Flux out: 1449 lm

FACTSHEET

DMX channels	2, 3 or 7 channels
Beam angle	25°
Power supply	100 - 240 VAC
Power consumption	Max. 90 Watt
Cooling	Convection / no fan
DMX connection	3p XLR in & out
Dimensions	300 x 255 x 205 mm (hxxwxd)
Weight	4 Kg
Certification mark	CE
Article number	156000
Included items	Power cable, Filter Frame
IP rating	IP22