

Highlights:

- 360° LED light bar
- Transparent window for name tag (4x)
- 4 programmable touch buttons (with LED)
- Rotary encoder
- Compatible with most TCP-IP supported AV equipment

Product information:

The DWP105 is a universal network wall panel controller, which is operated through 4 capacitive touch buttons and a rotary encoder dial. Each button is provided with an RGB indicator LED, while the RGB LED ring gives the user feedback on the selected settings and audio VU information.


The front panel is finished with high-grade materials such as the hardened glass makes them blend into any environment. These wall panels are compatible with standard EU style in-wall boxes, these wall panels are the ideal solution for solid and hollow walls.

The IP based communication makes it future proof while also being backwards compatible with a lot of existing products, while the limited PoE power consumption makes it compatible with any PoE network-based installation.

Each button is provided with a transparent window that allows a custom name tag to be added behind the panel, offering a neat finishing while having a clear overview of the configured functions.

The configuration of the button functions and the rotary dial is fully flexible, with full compatibility and support for a wide variety of devices. The simultaneous multi-device support offers the largest flexibility for numerous specific applications.

The DWP105's design allows it to be used in many applications and with many different AUDAC or third-party AV equipment. From amplifiers to speakers, the choice is yours.



System specifications:

Control		4 programmable touch buttons (transparent window name tag)
		Rotary encoder
Indicators		RGB LED's (each button)
		360° RGB LED light bar (16 LED)
Configurable settings		Fully configurable button & rotary functions - Routing
		Fully configurable button & rotary functions - Volume up / down
		Fully configurable button & rotary functions - Mute
		Fully configurable button & rotary functions - Toggle relay
Configuration		Audac Touch™
Power	Supply	PoE powered (IEEE 802.3at)
Connectors		RJ45 (network + PoE)

Product Features:

Dimensions			80 x 80 mm (W x H) (Remote wall panel)
Colours			Black (RAL9005) (DWP105/B)
			White (RAL9003) (DWP105/W)
Front finish			Elegant ABS front panel with glass
Accessories	Optional	Surface mount Installation boxes	WB200 - Surface mount wall box for WP & DWP series
		Flush mount Installation boxes	Flush mount box for 45 x 45 mm wall panel - Solid wall - WB45S/FS
			Flush mount box for 45 x 45 mm wall panel - Hollow wall - WB45S/FG
Construction			ABS
Installation standard			Compatible with EU installation materials

Variants:

- DWP105/B - Black version
- DWP105/W - White version