

Product Detail Page



PA-12040

Number: 17.3390

4-zone mono mixing amplifier,

with professional features for universal multi-room PA applications.

- 4 x 120W_{RMS}, 100V and 4 Ω / 8 Ω operation
- Perfect utilisation of the capacity and reliable protection of the connected speakers due to an integrated limiter
- 3 inputs microphone/line via comb. jacks
- 2 inputs line stereo via RCA jacks
- Each input channel with gain control, 2-way tone control, channel mute switch and routing switch for zones
- Microphone inputs with +46V phantom power, can be switched on additionally as required
- Priority function for channels 1-3, switchable
- Independent paging input, can be routed to all zones
- 4 zone outputs, can be controlled individually
- Zone and monitor line outputs for additional amplifiers or recorders
- Connection for monitor speakers
- Level control via VU meters for zone and monitor
- Adjustable headphone output
- Fan-cooling
- 230V mains operation

100V 4 Ω 8 Ω



Technical Facts

Output power	4 x 120W _{RMS} 4 x 170W _{MAX}
Mic/line	5mV/4k Ω , 100mV/10k Ω 100mV/30k Ω
Telephone paging	40mV/5k Ω
Speakers	4 x 25V/70V/100V, 4 Ω /8 Ω
Monitor speakers	8 Ω /1W
Line (zone)	1.7V, bal.
Line (mix out)	3.95V
Frequency range	50-17,000Hz
Bass	\pm 10dB/100Hz
Treble	\pm 10dB/10kHz
S/N ratio, mic	> 65dB
S/N ratio, line	> 75dB
THD	< 1%
Admiss. ambient temp.	0-40 °C
Power supply	230V~/50Hz/1,200VA
Dimensions	482x133x410mm, 3RS
Weight	20.5kg
Mic/line	3 x 6.3mm/XLR comb. jack, bal. 2 x RCA L/R
Paging	screw terminal
Priority	screw terminal
Line (zone)	screw terminal
Line (mix out)	screw terminal
Headphones	3.5mm stereo jack
Speakers (monitor)	screw terminal
Speakers (zone)	screw terminal
Power supply	3-pin IEC jack

