

Product Detail Page



PA-4040MPX

Number: 17.3450

4-zone mixer,
for general multiroom PA applications.

- 4 zones with routing facility of all input channels as desired
- 3 inputs microphone/line via comb. jacks
- 2 inputs line stereo via RCA jacks
- Each input channel with gain control, 2-way tone control and zone routing switch
- Microphone inputs with +15 V phantom power, to be switched on as required
- Priority function for channels 1-3, switchable
- Independent paging input, can be routed to each zone
- 4 zone outputs, can be adjusted individually
- Connection for monitor speaker
- Level control via zone VU meter and monitor VU meter
- Adjustable headphone output
- Mains operation or 24 V emergency power operation

Technical Facts

Mic/line 1-3	5 mV/4 k Ω , 100 mV/10 k Ω
Line 4-5	100 mV/30 k Ω
Telephone paging	40 mV/5 k Ω
Line (zone)	1.7 V, bal.
Line (mix out)	3.95 V
Monitor speakers	8 Ω /1 W
Frequency range	50-17,000 Hz
Bass	\pm 10 dB/100 Hz
Treble	\pm 10 dB/10 kHz
Mic	> 65 dB
	> 75 dB
THD	< 1 %
Admiss. ambient temp.	0-40 °C
Power supply	230 V~/50 Hz/20 VA, 24 V = /600 mA
Dimensions	482x133x220 mm, 3 RS
Weight	4.5 kg

