

## Product Detail Page



### PA-4240

Number: 17.0820

#### PA power amplifiers

- 4 x 240W<sub>RMS</sub> (PA-4240)
- 4 x 120W<sub>RMS</sub> (PA-4120)
- Routing switches for parallel operation on 2 channels each
- Temperature-controlled fan
- Connection for external on/off switch
- LED display for clip, protect, excess temperature and output level
- Mains operation or 24V emergency power operation

## Technical Facts

<b>Output power</b>	4 x 240W <sub>RMS</sub>
<b>Input sensitivity</b>	1.2V, bal.
<b>Output impedance</b>	31V/4Ω , 50V/10.4Ω , 70V/20Ω , 100V/42Ω
<b>Frequency range</b>	55-17,000Hz, -3dB
<b>S/N ratio</b>	> 90dB, A-weighted
<b>THD</b>	< 1%
<b>High-pass filter</b>	
<b>Admiss. ambient temp.</b>	0-40 °C
<b>Power supply</b>	230V~/50Hz/2,720VA,24V = /113A
<b>Dimensions</b>	483x133x370mm, 3RS
<b>Weight</b>	28kg
<b>Connections</b>	
<b>Signal input</b>	4 x XLR
<b>Speaker output</b>	screw terminals
<b>Other features</b>	

