

# Product Detail Page



## SA-250/SW

Number: 25.3390

### Universal stereo mixing amplifier

Sing along! The clearly arranged user surface of the SA-250/SW makes listening to music and especially making music really enjoyable. One of the three stereo line sources at a time and three mono microphone sources can be mixed together without any problems. When combined with special karaoke CDs or DVDs, features like one-touch karaoke or vocal partner are available. An adjustable digital echo can be added to the microphone channels as an effect. The fanless cooling concept of the amplifier ensures a silent operation. The latest protective circuits provide protection against overload, overheating and short circuit.

- 200W<sub>MAX</sub>
- Silent operation due to fanless cooling concept
- 3 stereo line inputs
- 3 mono microphone inputs on the front panel, each with gain control
- Adjustable digital echo for the microphone inputs
- Karaoke feature
- Vocal partner feature
- LEDs for level control and active line inputs
- Controls for volume, bass, treble, balance and digital echo
- Stereo record output
- 482mm (19") rack installation, 1RS, with supplied mounting brackets



## Technical Facts

### Output power

---

**Max. power** 2 x 100W<sub>MAX</sub>

---

### RMS power

---

**Stereo 4?** 2 x 50W<sub>RMS</sub>

---

**Stereo 8?** 2 x 30W<sub>RMS</sub>

---

### General information

---

**Inputs** 175mV/8k $\Omega$  (line) 2.5mV/3.5k $\Omega$  (mic)

---

**Frequency range** 20-20,000Hz

---

**S/N ratio** 62dB

---

**Digital echo** 200ms

---

**Equalizer** bass:  $\pm 10$ dB treble:  $\pm 10$ dB

---

**Power supply** 230V~/50Hz/210VA

---

**Admiss. ambient temp.** 0-40 °C

---

**Dimensions** 432x45x275mm

---

**Weight** 4.5kg

---

**Connections** line: RCA L/R mic: 6.3mm jack rec.: RCA L/R speaker:  
spring-load. speaker term.

---

