



Visit product page



CLIMATE C5

L005753

High quality ceiling speaker for pro audio and public address, 100/70V and 8 \bar{U} selecting switch, polypropylene woofer 4", superior tweeter 1", frequency response 80Hz - 23kHz, 87 dB Spl, Hole size 175mm.

TECHNICAL DETAILS

Technical Specifications

Rated Power: 20 Watt @ 100 Volt, 30 Watt @ 8 \bar{U} .

Max Power: 30 Watt @ 100 Volt, 45 Watt @ 8 \bar{U} .

Impedance: 250 \bar{U} , 500 \bar{U} , 1 k \bar{U} , 2 k \bar{U} , 4 k \bar{U} .

Constant power:

- 100V: NC, 20W, 10W, 5W, 2,5W.

- 70V: 20W, 10W, 5W, 2.5W, 1,25W.

SPL (1W/1m): 87dB.

Max SPL (Rated/1m): 102 dB @ 100 Volt, 103 dB @ 8 \bar{U} .

Frequency Response: 80Hz - 23 kHz.

Spread angle: 70° - 140°.

Power selection with rotary switch.

Made of ABS material with iron mesh.

Operating temperatures: -20°C ~55°C; <95%.

Speakers Unit: 4" Bass + 1" Treble.

Size: Ø205 x180H mm.

Hole size: Ø175mm.

Weight: 2,6 Kg.

Installation: 4 claw rotatable mounted ear.


Gross weight: 24.5 Kg, 8 pieces.

Packing size: 45 x 45 x 46 cm, 8 pieces.

PHOTOS



PRODUCT VIDEO



www.fos-lighting.eu

