



Visit product page



CLIMATE C8

L005755

High quality ceiling speaker for pro audio and public address, 100/70V and 8 \bar{U} selecting switch, polypropylene woofer 6", superior tweeter 1", frequency response 53Hz - 23kHz, 90 dB Spl, Hole size 230mm.

TECHNICAL DETAILS

Technical Specifications

Rated Power: 60 Watt @ 100 Volt, 90 Watt @ 8 \bar{U} .

Max Power: 90 Watt @ 100 Volt, 120 Watt @ 8 \bar{U} .

Impedance: 83 \bar{U} , 167 \bar{U} , 333 \bar{U} , 666 k \bar{U} , 1.3 k \bar{U} .

Constant power:

- 100V: NC, 60W, 30W, 15W, 7.5W.

- 70V: 60W, 30W, 15W, 7.5W, 3.75W.

SPL (1W/1m): 90dB.

Max SPL (Rated/1m): 109 dB @ 100 Volt, 110 dB @ 8 \bar{U} .

Frequency Response: 53Hz - 23 kHz.

Spread angle: 50° - 100°.

Power selection with rotary switch.

Made of ABS material with iron mesh.

Operating temperatures: -20°C ~55°C; <95%.

Speakers Unit: 6" Bass + 1" Treble.

Size: Ø265 x2205H mm.

Hole size: Ø230mm.

Weight: 4,2 Kg.

Installation: 4 claw rotatable mounted ear.

Gross weight: 19.7 Kg, 4 pieces.

Packing size: 60 x 60 x 28 cm, 4 pieces.

PHOTOS



PRODUCT VIDEO



www.fos-lighting.eu

