



Visit product page



DP2006

L005739

Professional audio processor 2 input/ 6output, 96KHz sampling frequency, 32bit DSP, 24bit A/D and D/A converter, 8 bands PEQ, delay up to 1000ms, HPF and LPF filters, wifi access point, PC software and tablet IOS and Android application.

TECHNICAL DETAILS

Features

- DP series, a professional audio processor.
- 96 kH sampling frequency, 32-bit DSP processor, 24-bit A/D and D/A converter.
- 8 bands PEQ, Gain (+/- 20dB), delay up to 1000 ms, polarity and mute for each channel.
- Lo-shelf and Hi-shelf for output channels.
- HPF/LPF: 12dB, 18dB, 24dB or 48dB.
- Crossover type: Bessel, Butterworth, Linkwitz-Riley.
- Channel copy function for Input/Output channels.
- 20 groups of users settings. Central control support.
- WiFi, USB, RS232 interfaces.
- Equipped with professional PC software.

Technical specifications

- 2 Input / 6 Output channels.
- Input impedance: 20 k Ω .
- Output impedance: 100 Ω .
- 1x USB port.
- CMRR: >70 dB (1 kHz).
- Impot range: \leq +18 dBu.
- Frequency: 20 Hz - 20 kHz (-0.5 dB).
- S/N: >110 dB.

THD: <0,01 % Output= 0dBu / 1 kHz.

Separation: >80 dB (1 kHz).

Input channels:

Mute

Delay adjustment range: 0 - 1000 ms.

Polarity - in phase (+) & reversed phase (-).

PEQ: 8 bands PEQ, Freq: 20 Hz - 20 kHz, bandwidth 0,05 - 3 oct. Step: 0,05 oct, Gain +/- 20 dB, Step: 0,1 dB.

Output channels:

Mute

Select: each output channel can be select different input channels, you can select any combination of input channels.

Gain: adjustment range: 12dB, step: 0,1 dB.

Delay adjustment range: 0 - 1000 ms.

Polarity - in phase (+) & reversed phase (-).

PEQ: Each output channel with 8 bands PEQ and 3 modes: PEQ/Lo-shelf/Hi-shelf.

Frequency: LPF, HPF, mode: Linkwitz - Riley/Bessel/Butterworth, FREQ: 20 Hz - 20 kHz, Slope:12dB/oct, 18dB/oct, 48dB/oct.

Limiter: Gate level: 20dB, step: 1dB, start time: 0,3 ms - 100 ms, <1 ms, Step: 0,1 ms>, 1ms, Step: 1 ms Release Time is the 4, 8, 16, 32 times of the start time.

Processor: 96 kHz sampling frequency, 32-bit DSP chip processor, 24-bit A/D and D/A converter.

Consumption: <25W.


Power input: 110 / 240 Volt AC, 50/60 Hz.

Gross Weight: 3,15 Kg.


Package dimensions: 57 x 26 x 9 cm.

Applications for iPad & Windows PC

app download



[Download for Windows PC](#)




PHOTOS



PRODUCT VIDEO





www.fos-lighting.eu

